Wireless M2M Solution Leader

WM-300은 10/5Mbps(D/U)속도의 LTE Cat.1bis를 지원하는 외장형 모뎀입니다.
30핀 헤더 커넥터를 통해 PCB에 직접 장착되어 케이블이 필요없습니다.
UART 인터페이스를 통해 AT커맨드로 모뎀을 제어하여 SMS, DATE, 음성 사용 가능합니다.
고객은 추가적인 통신사 인증없이 개통 후 사용할 수 있습니다.

WM-500

Semi-External Modem

B2B-Connector-Type
LTE Cat.1 bis Semi-External





Actual Size

WM-500

Description

Frequency / Standard	LTE Cat.1 bis, Band 3/5
Connector	30 Pin Header Connector
Antenna	MCX Antenna Connector
Serial interface	TTL 3.3V UART
USIM	1.8/3.0V Mini SIM (2FF)
Dimensions	46(W) x 60(H) x 11(T) mm
Weight	47g
Supply Voltage	DC 5V
Power Consumption	≤600mA(Max Power), ≤60mA(IDLE State)
Temperature Range	-20℃~+60℃ (operating), -40℃~+80℃ (storage)
Data Speed	10Mbps/5Mbps(Down/Up)
Data Features	Embedded TCP/IP, FTP, HTTP(S), PPP, MQTT
SMS Features	Point-to-Point MO/MT
Voice Features	Volte
Certifications	SK Telecom / KC
Accessory	SMA Dipole Antenna MCX-to-SMA Gender Cable

M2M net
WIRELESS M2M SOLUTION LEADER

(주)앰투앰넷
[14067] 경기도 안양시 동안구 평촌대로212번길 55
(관양동, 대고빌딩 10층)
Tel : 031-387-3311
Fax : 031-387-3811
E-mail : sales@m2mnet.net
www.m2mnet.net

개통문의 : (주)앰투앰넷

Machine to Machine